

VALONA MS 1046



Metalworking



Chlorine-free neat cutting oil for non-severe machinings.

UTILISATIONS

- **VALONA MS 1046** is a **chlorine-free neat cutting oil dedicated to** both ferrous and non-ferrous metals.
- **VALONA MS 1046** is widely used on cutting operations such as screw-cutting on copper alloys, on low-carbon steels and non alloyed steels.

ADVANTAGES

- Good anti-wear **performances**.
- Good anti corrosion and antifoam (silicon-free) properties.
- **Excellent compatibility with seals and paintings.**
- Excellent filterability.

TYPICAL CHARACTERISTICS	METHODS	UNITS	VALONA MS 1046
Appearance	-	-	Clear liquid
Colour	-	-	Yellow
Density at 15°C	ISO 3675	kg/m ³	877
Cinematic viscosity at 40°C	ISO 3104	mm ² /s	46
Copper corrosion	ISO 2160	-	1a
Open cup flash point	ISO 2592	°C	230

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

13 november 2002

VALONA MS 1046

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from

www.quick-fds.com.

