

# MARTOL LVG 25 AQ



*Metalworking*



VOC free metal forming vanishing oil.

## UTILISATIONS

- **MARTOL LVG 25 AQ** is an evaporating oil for low and medium severity drawing on steel and non-ferrous metals.
- **MARTOL LVG 25 AQ** can be applied with a brush, by spraying or with a roller.
- **MARTOL LVG 25 AQ** is thermally degreaseable, does not leave any residu over 220 °C.
- **MARTOL LVG 25 AQ** is recommended for brazing assembly lines.

## ADVANTAGES

- **MARTOL LVG 25 AQ** is a VOC free product.
- **MARTOL LVG 25 AQ** is characterised by:
  - His evaporating character.
  - A good wetability of the lubricant which assure an excellent surface covering
  - Can be used in certain cases on coated metal.
  - Leaves a thin film and degreasing operation is most of the time unnecessary.
- **MARTOL LVG 25 AQ** ensures extended tool life.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL LVG 25 AQ
Color	Visual	-	Clear
Viscosity at 20°C	NFT 60-100	mm <sup>2</sup> /s	4.4
Viscosity at 40°C	NFT 60-100	mm <sup>2</sup> /s	2.8
Density at 25 °C	EN ISO 12185	kg/m <sup>3</sup>	824
Flash point	EN 22719	°C	111

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS  
INDUSTRIE**

4-02-2014 (supersedes 31-10-2013)

MARTOL LVG 25 AQ

1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).