

# FINADET SW



**TOTAL**

*Special detergent for washing machines*

## UTILISATIONS

| APPLICATIONS                   | PERCENTAGE FOR UTILISATION                      |
|--------------------------------|---|
| Cleaning mechanical components | Pure or diluted, according to degree of soiling |

## PERFORMANCES

- Very powerful rejecting detergent for grease and scale removal.
- It can be used cold or hot, by low, medium and high pressure spraying.
- No foaming.
- Anticorrosion properties from 2% in water, it protects the cleaned parts between operations.
- It can be used for dipping in combination with ultrasonic cleaning.

## ADVANTAGES

- **FINADET SW** is a washing product. The absence of flash point ensures optimal safety conditions.
- Absence of chlorinated molecules.

| TYPICAL CHARACTERISTICS       | METHODS         | UNITS             | FINADET SW |
|-------------------------------|-----------------|-------------------|------------|
| Appearance                    | Visual          |                   | Clear      |
| Colour                        | Visual          |                   | Yellow     |
| Physical state                | Visual          |                   | Liquid     |
| Density at 25 °C              | NF EN ISO 12185 | Kg/m <sup>3</sup> | 1056       |
| Odour                         | Olfactory       |                   | none       |
| pH at 5%                      | -               |                   | 8.6        |
| pH pure at 20°C               | -               |                   | 9.2        |
| Pour point                    | ISO 3016        | °C                | - 6        |
| Refraction index              | ASTM D 1218     |                   | 1.4220     |
| Surface tension at 5% at 25°C | ISO 6295        | dynes/cm          | 29         |

The values of the characteristics featured on this table are typical values given as indications only.