

# MARTOL EP 360



*Metalworking*



**Viscous oil for difficult pressing.**

## UTILISATIONS

- Pressing, difficult forming of alloyed steels or stainless steels.
- This product is suitable for the stamping of sheet metal.

## ADVANTAGES

- Very viscous mineral.
- Very good extreme-pressure properties.
- Excellent unctuousness.
- Very good anti-wear property to ensure long tool life.
- Easy degreasing.

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL EP 360
Colour	Visual		5.5
Density at 15°C	ISO 3675	kg/m <sup>3</sup>	978
Viscosity at 40°C	ISO 3104	mm <sup>2</sup> /s	362
Cleveland flash point	ISO 2592	°C	> 220
Sulfated ashes	ISO 3993	% weight	1.35
Copper corrosion	ISO 2160	-	1b

Above characteristics are mean values given as an information.

**TOTAL LUBRIFIANTS**  
**Industrie & Spécialités**

27 july 2001  
MARTOL EP 360  
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.  
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser [www.quick-fds.com](http://www.quick-fds.com).