

GRAISSE N4128



Lubricating Grease



Calcium grease for vehicle body parts.

APPLICATIONS

Automotive applications

Recommendations

- Non-staining grease for vehicle body parts, door hinges, locks, linkages, door springs.
- Static protection of electrical connexions.
- Always avoid contamination of the grease by dust and/or dirt when applying. Preferably use a pneumatic pump or cartridges to apply the product.

SPECIFICATIONS

- ISO 6743-9: L-XDAEA 1
- DIN 51502: K1G-40
- Approved by PSA PEUGEOT CITROEN

ADVANTAGES

Adhesive calcium grease
Low temperature grease
Excellent antirust protection

Harmful substances free

- Good mechanical stability, even in the presence of water.
- Non staining for paints.
- Excellent low temperature performances.
- Excellent antirust protection.
- **GRAISSE N4128** does not contain lead, or any other heavy metals considered harmful to human health and the environment.

TYPICAL CHARACTERISTICS	METHODS	UNITS	GRAISSE N4128
Soap/Thickener		-	Calcium
NLGI Grade	ASTM D 217/DIN 51 818	-	1
Color	Visuelle	-	Beige
Appearance	Visuelle		Smooth, tacky
Operating Temperature range		°C	- 40 à +80
Base oil viscosity at 40°C	ISO 3104	mm²/s	79
Worked penetration at 25 °C	ASTM D 217/DIN51 818	1/10 mm	305-345
Penetration at -30°C	NFT 60-171	mm	170
Antirrust performance SKF EmCor	DIN 51 802/IP220/NFT 60-135/ISO 11007	rating	0-0
Dropping point	IP 396/NFT 60 102 C	°C	140

Above characteristics are mean values given as an information