

DRASTA C 1500



Metalworking



Cold quenching oil.

UTILISATIONS

- Cold quenching oil for routine applications.
- Quenching of bulky, simple-shaped parts made of medium or high-alloy steels with good hardening capacity.
- Quenching of case-hardened or nitrided steels.
- Working temperature : 30°C to 80°C.
- All types of furnaces with separate or built-in tanks.

ADVANTAGES

- Excellent resistance to oxidation and thermal changes owing to:
 - the use of solvent-refined base oils,
 - the presence of effective and durable antioxidant additives which give long bath life.
- High flash point to ensure risk-free operation in the utilisation temperature range.
- Low volatility limits evaporation loss and the formation of vapours and fumes.
- **DRASTA C 1500** is fully compatible with all quenching oils in the **TOTALFINAELF** product range.

TYPICAL CHARACTERISTICS	METHODS	UNITS	DRASTA C 1500
Density at 15°C	ISO 3675	kg/m ³	878
Colour	Visual	-	2
Viscosity at 40°C	ISO 3104	mm ² /s	20
Viscosity at 100°C	ISO 3104	mm ² /s	4
Cleveland flash point	ISO 2792	°C	200
Neutralization index	ISO 6618	mgKOH/g	< 0,1

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

23 july 2001
DRASTA C 1500
1/1



This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.
A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.