

MARTOL EP 5 CF



Metalworking



Fluid pressing oil

UTILISATIONS

- Pressing, hard forming of ferrous metals and aluminium alloys.
- Application : using roller, brush or by low pressure spraying.

ADVANTAGES

- Very fluid mineral oil doped without any additive containing chlorine.
- Very high extreme-pressure properties.
- Very good wettability of the blank.
- Good corrosion protection properties

TYPICAL CHARACTERISTICS	METHODS	UNITS	MARTOL EP 5 CF
Appearance	Visual	-	Limpid liquid
Colour	Visual	-	Light brown
Density at 15°C	ISO 3675	kg/m ³	857
Viscosity at 40°C	ISO 3104	mm ² /s	3,21
Flash point	ASTM D93	°C	> 120
4 balls welding load	ASTM D2783	Kg	800
4 balls wear	ASTM D2266	Mm	0,38
Falex EP	ASTMD D3233	Lbs	3100

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS
Industrie & Spécialités

5 September 2001

MARTOL EP 5 CF

1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. is obtainable via your commercial adviser www.quick-fds.com.

