


# LUBRILAM C6



Metalworking



Concentrate of performance additives for aluminium rolling oils.

## UTILISATIONS

- Concentrate of additives designed for the doping of the bases used in the rolling of aluminium alloys.
- **LUBRILAM C6** meets the requirements of the FDA CFR 178.3910.

## ADVANTAGES

- Light mineral base containing a high concentration of «ester»-type additives.
- Ease of dissolution.
- Makes it possible to improve the quality and production capacity of the rolling mills.
- Higher quality of the finished product.
- Increase in the service life of the rolling oil.

| TYPICAL CHARACTERISTICS | METHODS  | UNITS              | LUBRILAM C6 |
|-------------------------|----------|--------------------|-------------|
| Appearance              | visual   | -                  | clear       |
| Density at 15°C         | ISO 3675 | kg/m <sup>3</sup>  | 862.5       |
| Colour                  | visual   | -                  | 0/0.5       |
| Viscosity at 40°C       | ISO 3104 | mm <sup>2</sup> /s | 2.29        |
| PM flash point          | ISO2719  | °C                 | 120         |

The values of the characteristics listed in this table are typical values given as an indication.

**TOTAL LUBRIFIANTS**  
Industrie & Spécialités  
20-11-2012 (supersedes 20-03-2007)  
LUBRILAM C6  
1/1

Ce lubrifiant utilisé selon nos recommandations et pour l'application pour laquelle il est prévu ne présente pas de risque particulier.  
Une fiche de données de sécurité conforme à la législation en vigueur dans la C.E. est disponible sur [www.quick-fds.com](http://www.quick-fds.com) et auprès de votre conseiller commercial.

