

CAPRANO TDJ 15W-40



Synthetic "low- SAPS" lubricant for industrial Diesel engines.

SPECIFICATIONS AND APPROVALS

International specifications	ACEA E9/E7	API CJ-4	
Manufacturers' approvals	Meets the requiremen	nts of	
✓ Cummins CES 20081 ✓ Volvo VDS-4	✓ Caterpillar ECF-3 / ECF-2 / ECF-1a		

APPLICATIONS

TOTAL CAPRANO TDJ 15W-40 is a high-performance lubricant used in industrial Diesel engines.

The use of this lubricant is linked to the mandatory use of ultra low sulfur fuel (<50 ppm).

With its "low-SAPS" (low sulphated ash, phosphorus and sulphur) technology, TOTAL CAPRANO TDJ 15W-40 is specifically adapted to the latest generation of Diesel engines equipped with **post-treatment systems**, such as Diesel particulate filters (DPFs).

TOTAL CAPRANO TDJ 15W-40 is also suitable for engines with selective catalytic reduction systems.

PERFORMANCES AND CUSTOMER BENEFITS

High quality base stocks combines combined with high-performance additives make TOTAL CAPRANO TDJ 15W-40 an exceptional **technical performances** lubricant and sustainable over time.

Advanced additives keep the engine's most sensitive parts clean thanks to **detergent**, **dispersant and anti-wear properties**, added to effective control of soot, sludge and deposits.

The "low-SAPS" formulation of TOTAL CAPRANO TDJ 15W-40 improves the post-treatment system durability, preventing the clogging of the Diesel particulate filter (DPF).

PHYSICAL AND CHEMICAL CHARACTERISTICS*

TOTAL CAPRANO TDJ 15W	<i>I</i> -40	Method	Value
Density at 15°C	kg/m ³	ASTM D1298	876
Kinematic Viscosity at 40°C	mm²/s	ASTM D445	121
Kinematic Viscosity at 100°C	mm²/s	ASTM D445	15.8
Viscosity Index	-	ASTM D2270	138
Pour point	°C	ASTM D97	-36
T.B.N	mgKOH/g	ASTM D2896	8.5
Sulphated Ash	% m/m	ASTM D874	0.98

^{*} The features mentioned above are average values obtained with some variability in production and do not constitute a specification.



92029 Nanterre cedex FRANCE **TOTAL CAPRANO TDJ 15W-40**

Update 07/2014 www.lubricants.total.com