

LESANA SC 900



Metalworking



Ultra concentrate for production of a concentrate for making micro-emulsion without chlorine for grinding and machining of ferrous and non ferrous metals, for regular to very difficult operations.

APPLICATIONS

- **LESANA SC 900** is specifically dedicated to be mixed to base oil, in order to be used for regular to very difficult machining operations of ferrous and non ferrous metals.
- **LESANA SC 900** can also good results in plane cylindrical or centerless grinding once mixed in good proportions with base oil.

SPECIFICATIONS

ISO 6743/7

- ISO-L MAE

ADVANTAGES

- Very easy production of a concentrate of soluble fluid, adding **LESANA SC 900** in base oil in good proportions. Please refer to **TOTAL LESANA** recommendations.
- **LESANA SC 900** will offer excellent stability in service and non foaming properties.
- **LESANA SC 900** will provide good corrosion protection of machine parts and machines

HEALTH AND SAFETY

- **LESANA SC 900** contains no chlorine, nitrite, PTBB, NPE or DEA.
- **LESANA SC 900** has no particular smell.

TYPICAL CHARACTERISTICS	METHODS	UNITS	LESANA SC 900
Appearance	Visual	-	Clear
Density at 15°C	ISO 3675	kg/m ³	1150
Kinematic viscosity at 20 °C	DIN 51562	mm ² /s	21.5
Refractometric correction factor	-	-	1.42

The properties given in this table are typical values provided as an illustration.